

# NEW F340e Fireproofing Pump

## NKC PACKAGE



### Benefits of New UPGRADED F340e

- ♦ Improved spray performance **up to 20 bags an hour**
- ♦ Tool-less pump design for easy knockdown and service
- ♦ Long lasting, all stainless steel pump components
- ♦ Shorter, reduced number of repair parts in pump lower
- ♦ Tool-less inlet boot clamps for easy disassembly
- ♦ More robust remote switch connector, similar to F800e

[CLICK HERE TO WATCH VIDEO](#)

## NKC PACKAGE



### NKC Compressor

- ♦ EXCLUSIVE PACKAGE DEAL!
- ♦ Direct Drive Piston, 2.5 HP, 6.5 CFM



### Nozzle Assembly

- ♦ 1", with 24" aluminum pole



### Hose Package

- ♦ 1 1/2" x 25', 1 1/4" x 25', 1" x 50', 1233 PSI, Airline, Reducer, & Steel Kamlocks

## SPECIFICATIONS

Pump type	2-ball piston
Max working pressure	600 psi
Max spray pressure	500 psi
Max output*	Up to 20 bags/hour
Volume control	Variable
Max hose length	1" dia x 100 ft (30.5 m)
Conveying distance	Up to 50 ft (15 m) Vertically
Hopper capacity	20 gal (76 L)
Hopper opening	22.5" W x 14" D
Hopper/filling height	26 in
Pump outlet size	1" cam groove
Dimensions	45.5" L x 24" W x 38" H
Weight	210 lb (without hose and applicator)
Chemical compatibility	Water based materials
Wetted parts	SST, aluminum, carbide seats, plated steel, PTFE, UHMWPE, LLDPE, urethane, solvent-resistant elastomer
Remote on/off switch	Optional
Air compressor	Optional

\* Tested with high density cementitious fireproofing material. Performance will vary based on material, mix consistency, hose size and other factors.

## INCLUDES TECHNICAL SUPPORT

Nathan Kimmel Co, LLC, 4876 Alhambra Ave., Los Angeles, CA 90032

**800.421.0005 ♦ [www.NATHANKIMMEL.com](http://www.NATHANKIMMEL.com) ♦ [sales@nathankimmel.com](mailto:sales@nathankimmel.com)**

Proud Members of

